



NO LIMIT SEALING

YOUR COMPLETE GUIDE TO DRIVEWAY SEALING AFTERCARE

FROM THE EXPERTS AT NO LIMIT SEALING



Asphalt



Interlock



Concrete

www.nolimitsealing.com
info@nolimitsealing.com
+1-416-845-5193

Welcome to No Limit Sealing's Premium Driveway Sealing Aftercare Guide

Your driveway is one of the most important visual and functional parts of your home. Proper aftercare ensures its long-term protection, improved curb appeal, and increased property value. This guide will walk you through best practices for maintaining your asphalt, interlock, or concrete driveway year-round.

Pro Tip: Review this guide before each season for easy maintenance and long-term protection.

Asphalt Driveway Aftercare

Understanding Asphalt Sealing

Asphalt sealing protects your driveway from sunlight, rain, and daily wear. The sealer bonds to the surface to prevent oxidation, cracking, and water penetration.

Immediate Aftercare

- Avoid all traffic for 48–72 hours after sealing.
- Prevent debris, water, or oil from contacting the surface.
- Keep pets and children away until fully cured.

Ongoing Maintenance

- Sweep regularly to remove dirt and grit.
- Clean small stains with mild soap and water.
- Reseal every 2–3 years for consistent protection.



Pro Tip: On very hot days, avoid parking in the same place repeatedly to prevent softening.

Interlock Driveway Aftercare

Understanding Interlock Sealing

Sealing interlock enhances the colour of the stones and protects the joints from erosion, weed growth, and shifting. Proper maintenance will preserve its vibrancy and structure.

Maintenance Tips

- Stay off the surface for 24 hours after sealing.
- Sweep joints regularly and refill polymeric sand when necessary.
- Avoid high-pressure washing that can dislodge joint sand.
- Reseal every 2–4 years to maintain the finish.

Pro Tip: Sweep joint sand after every heavy rainfall to prevent erosion and weed regrowth.

Concrete Driveway Aftercare

Why Sealing Matters

Concrete is porous and prone to absorbing water and stains. A proper sealer prevents penetration from oils, salts, and freeze–thaw damage.

Care Instructions

- Avoid walking or driving on the surface for 48 hours after sealing.
- Use mild soap and water for cleaning — never bleach or acids.
- Avoid de-icing salts during winter; use sand instead.
- Reseal every 3–4 years.

Pro Tip: Seal your concrete before winter to prevent damage caused by Ontario’s freeze–thaw cycle.

Maintenance Comparison Table

Driveway Type	Reseal Frequency	Expected Lifespan	Maintenance Level
Asphalt	Every 2–3 Years	20–25 Years	Low
Interlock	Every 2–4 Years	25–30 Years	Moderate
Concrete	Every 3–4 Years	30+ Years	Low

Warranty & Professional Care

At **No Limit Sealing**, we provide our Premium Aftercare Assurance to ensure your surface remains protected when our recommendations are followed.

What’s Covered:

- Protection against early wear for 24 months.
- Surface integrity under normal residential use.

Not Covered:

- Damage caused by neglect or harsh chemicals.
- Structural issues unrelated to sealing.



Pro Tip: Enroll in our annual maintenance program for guaranteed long-term protection and savings.

Contact No Limit Sealing

Website: www.nolimitsealing.com

Email: info@nolimitsealing.com

Phone: +1-416-845-5193

Service Areas: Toronto | Vaughan | Richmond Hill | Markham | Aurora | Newmarket | and More

Thank you for choosing No Limit Sealing — proudly serving the Greater Toronto Area with quality, care, and craftsmanship.